

Hybrid Inverter

3.6KW 5KW Single Phase Inverter




Inverter Features

- ✓ AC Coupled
Update existed solar on-grid system to hybrid
- ✓ Smart Load
Use Gen input as load output
- ✓ BMS
It can communicate with PYLONTECH, DYNESS etc brand battery
- ✓ Multiple Working Modes
Grid Tied, Hybrid or OFF Grid. Simultaneously manages power to/from Solar, Battery, Grid, Load and Generator
- ✓ Additional Feature
UPS time less than 5ms. Six stages time of use setting. Charge and discharge up to 125A 5KW(90A 3.6KW), load or home power first with zero export to grid.
- ✓ Six Time Of Use Settings, Peak Load Shifting.
- ✓ Smart generator start and night quiet mode.
- ✓ Support multiple parallel



Colour Touchscreen Display

Touchscreen interface as easy to understand as your phone. Simultaneously manages power to/from Solar Panels, Batteries, Grid, Load, and Generator.



Technical Specifications

Model	SUN-3.6K-SG0xLP1 -EU	SUN-5K-SG0xLP1 -EU
Battery Input Data		
Battery Type	Lead-acid or Li-Ion	
Battery Voltage Range (V)	40~60V	
Max.Charging Current (A)	90A	120A
Max.Discharging Current (A)	90A	120A
Charging Curve	3 Stages/Equalization	
External Temperature Sensor	Optional	
Charging Strategy for Li-Ion Battery	Self-adaption to BMS	
PV String Input Data		
Max.DC Input Power (W)	4680W	6500W
PV Input Voltage (V)	370V(100V~500V)	
MPPT Range (V)	125V-425V	
Start-up Voltage (V)	125V	
PV Input Current (A)	11A+11A	
No.of MPPT Trackers	2	
No.of Strings Per MPPT Tracker	1+1	
AC Output Data		
Rated AC Output and UPS Power (W)	3600W	5000W
Max AC Output Power (W)	3960W	5500W
Peak Power(off grid)	2 times of rated power, 10 S	
AC Output Rated Current(A)	15.7A	21.7A
Max.AC Current(A)	18A	25A
Max Continuous AC Passthrough(A)	35A	
Output Frequency and Voltage	50/60Hz; 220/230/240Vac(single phase)	
Grid Type	Single Phase	
Current Harmonic Distortion	THD<3%(Linear load<1.5%)	
Efficiency		
Max.Efficiency	97.60%	
Euro Efficiency	96.50%	
MPPT Efficiency	99.90%	
Protection		
PV Input Lightning Protection	Integrated	
Anti-islanding Protection	Integrated	
PV String Input Reverse Polarity Protection	Integrated	
Insulation Resistor Detection	Integrated	
Residual Current Monitoring Unit	Integrated	
Output Over Current Protection	Integrated	
Output Shorted Protection	Integrated	
Output Over Voltage Protection	Integrated	
Certifications and Standards		
Grid Regulation	VDE 0126,AS4777,NRS2017,G98,G99	
Safety Regulation	IEC62109-1, IEC62109-2	
EMC	EN61000-6-1, EN61000-6-3	
General Data		
Operating Temperature Range (°C)	-25~60 °C , >45 °C Derating	
Cooling	Fan	
Noise (dB)	<30	
Communication with BMS	RS485; CAN	
Weight (kg)	20.5KG	
Size (Length*Width*Height mm)	580×330×217mm	
Protection Degree	IP65	
Installation Style	Wall-mounted	
Warranty	5 years	